

Description:

The Fox Bollard is a spike mounted pathway light designed to provide an even wash of light to the walkways. Available in various colour temperatures, IP65, Machined Solid Brass (Aged), UV Stabilized Frosted Acrylic Diffuser, Brass Cable Gland, pre-itted double insulated exterior rated 500mm cable


Technical:

| | | | |
|--------------------|--------------------------|------------------|-----------------------------------|
| LED TYPE | COLORS D6240 | CONTROL GEAR | REMOTE |
| RATED POWER | 1W | DIMMING PROTOCOL | DALI - 0-10V - PHASE DIM - ON/OFF |
| CRI | 80 | CABLE LENGTH | 500MM STANDARD LENGTH |
| BEAM ANGLES | NOMINATED IN TABLE BELOW | MOUNTING OPTIONS | SPIKE |
| INPUT POWER | 24V DC CC | WEIGHT | ON REQUEST |
| NOMINAL LUMENS | 190lm | HARDWARE | ACRYLIC, CABLE GLAND, CABLE |
| IP RATING | IP65 | CONSTRUCTION | MACHINED SOLID BRASS |
| COLOUR TEMPERATURE | 2700K - 3000K - 4000K | WARRANTY | 2 YEARS |

Product Generator: example NL1607CV-AB-D-30-SP-1W-DALI-N/A

| Model | Finish | Beam Angle | CCT | Mounting | Wattage | Dimming | Accessory |
|----------|------------------|------------|----------|----------|-------------|---------|-----------|
| NL1607CV | AB Aged Brass | D Diffused | 27 2700K | SP Spike | 1W / 24V DC | DALI | N/A |
| | BR Brushed Brass | | 30 3000K | | | 0-10V | |
| | PB Black | | 40 4000K | | | Phase | |
| | PW White | | | | | On/Off | |
| | CC Custom | | | | | | |

| | | | | | | | |
|--------|---|---|---|---|---|---|---|
| NL1607 | - | - | - | - | - | - | - |
|--------|---|---|---|---|---|---|---|