

**Description:**

Recessed, deep baffled, Downlight, 4-6W CREE XLamp XHP-50 Gen 2, IP44 rated, Various colour temperatures and finishes available. Machined brass fitted with Cable gland, pre-fitted 500mm exterior rated power cable.



**Technical:**

LED TYPE	CREE XLamp XHP-50 Gen 2	CONTROL GEAR	REMOTE
RATED POWER	4W - 6W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	RECESSED - SURFACE WALL / CEILING
INPUT POWER / FORWARD VOLTAGE	350mA - 700mA / 8V	WEIGHT	0.2KG
NOMINAL LUMENS	465-990-lm	HARDWARE	GLASS LENS, O-RING, GLAND, CABLE
IP RATING	IP44	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

**Product Generator:** example 1629-PB-M-30-R-4W-1

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1629	AB Aged Brass	N Narrow 25°	27 2700K	R Recessed	4W / 350mA	1 DALI	1 Honeycomb Louver
	BR Brushed Brass	M Medium 30°	30 3000K	W Wall Mounted	6W / 700mA	2 0-10V	2 Diffuser Lens
	SS Stainless Steel	W Wide 47°	40 4000K	S Surface Mount		3 Phase	3 Elliptical Lens
	PB Black			F Floor		4 On/Off	4 Spread Lens
	PW White						
	CC Custom						

NL1629	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---