


## **TWIGGY SPOT SINGLE**


Data Sheet

## **Description:**

Belonging to the Twiggy family, the Twiggy Spot Double is a double directional spotlight with single wall bracket mounting supplied with a CREE XLamp XP-G3. Available in various colour temperatures, beam angles and finishes. IP65, Borosilicate Glass Lens, prefitted Honey Comb Baffle, pre-fitted 500mm lead.







## Technical:

LED TYPE	CREE XLAMP XP-G3	CONTROL GEAR	REMOTE
RATED POWER	2x 1W - 3W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE WALL / CEILING
INPUT POWER	24VDC	WEIGHT	ON REQUEST
NOMINAL LUMENS	2x 190lm - 380lm	HARDWARE	GLASS LENS, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example 1608-AB-M-30-F-1W-1-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1608	AB Aged Brass	N Narrow 10°	27 2700K	F Floor	1W / 24V DC	1 On/Off*	N/A
	BR Brushed Brass	M Medium 21°	30 3000K		3W / 24VDC		
	PB Black	W Wide 33°	40 4000K				
	PW White						
	CC Custom						

\*Dimming available on request

NI 1608 -						
INLIOUS -	-		-	-	-	-