

21003/160/DIM/NE Loop

design emiliana martinelli, 2017

Hanging lamp, diffused light, composed with curved modules and in white, black, peraly gold or copper colored extruded aluminium sectors. The union of those sectors offer different diameters rings, hanged by stainless steel cables. White opal polycarbonate diffuser. Integrated LED light source. Electronic dimmable Push/Dali, triac 5 fili, 0-10V e 1-10V driver inside in the ceiling stud. Available on request 2700K, 4000K.

interior light emission

21003/300/DIM Ø 300cm
composed by 4 sectors 90°

21003/200/DIM Ø 200cm
composed by 3 sectors 120°

21003/160/DIM Ø 160cm
composed by 3 sectors 120°


exterior light emission

21005/300/DIM Ø 300cm
composed by 4 sectors 90°

21005/200/DIM Ø 200cm
composed by 3 sectors 120°

21005/160/DIM Ø 160cm
composed by 3 sectors 120°

21003/160/DIM/NE loop

| | |
|-----------------|---|
| family: | LOOP |
| Designers: | Emiliana Martinelli |
| Utilization: | indoor |
| Typology: | pendant |
| Certifications: |  |
| Market: | This item is available in the following countries: EUROPE |

| | |
|---------------------|---|
| Body Color: |  other available colors |
| Diffuser Color: |  |
| Body Materials: | extruded aluminum |
| Diffuser Materials: | opal polycarbonate |

Dimensions

| | |
|-----------|--------|
| Width: | - |
| Height: | 8 cm |
| Length: | - |
| Depth: | - |
| Diameter: | 160 cm |

| | |
|----------------|-------|
| Hole Diameter: | - |
| Hole Depth: | - |
| Net weight: | 16 Kg |

Light Source



| | |
|----------------|----------|
| Watt: | 173W |
| Lumen: | 17000 lm |
| Light Source: | led |
| CRI: | >80 |
| duration: | 40000 |
| CCT: | 3000K |
| Energy degree: | A++ |

Device Specifications

| | | | | | |
|-------------------|----------|---------------------|--------|------------------------|--|
| Type of emission: | diffused | Power cable length: | - | Driver: | included |
| Power: | 171W | Steel cable length: | 3,5 cm | Power supply assembly: | external |
| Light output: | 11306lm | Glow Wire Test: | - | Power supply: | electronic dimmable power supply |
| Beam angle: | - | Impact Resistance: | - | Type of dimming: | push/dali, triac 5 fili, 0-10v e 1-10v |
| | | | | Voltage: | 230V |



technical drawing





Dimensions

Width: -
Height: 8 cm
Length: -
Depth: -
Diameter: 160 cm

Hole Diameter: -
Hole Depth: -
Net weight: 16 Kg

photometrics data



21003/300/DIM/BI LOOP 321W 3000K LED

