

LIGHTWAY 5 – OUTDOOR / WASHER BEAM

FLOOR MOUNTED, U BRACKET

The Lightway 5 Outdoor beam is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs. The Beam compatible with a wide array of beam angles, generating a powerful overall lighting effect.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptic
- Delivers High levels of light
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



Luminaire

Product Type: Washer
Body Material: Extruded aluminium


Optics

Optic Type: UV stabilized TIR Lens
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220–240 VAC 50/60 Hz
Control Gear Efficacy: > 85%



Polar Curve



Elliptical beam 10° x 54° /
LOR: 62.6%



Elliptical beam 10° x 54° /
LOR: 58.1%



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / WASHER BEAM

FLOOR MOUNTED, U BRACKET

We reserve the right to make technical changes without prior notice



projects@vicelighting.com – www.vicelighting.com

Lebanon 11-0125-Beirut +961 1 486311 – France 75012 Paris +33 06 75 32 73 23

LIGHTWAY 5 – OUTDOOR / WASHER BEAM

FLOOR MOUNTED, U BRACKET

Code Index:

<u>L 5</u>	<u>O</u>	<u>F 1</u>	<u>—</u>	<u>W T</u>	<u>E 1</u>	<u>— — — — —</u>	<u>—</u>	<u>6 5</u>	<u>— —</u>	<u>— — —</u>	<u>— —</u>
Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
			S			92701	C		BS	30	SI
			X			92702	D		WS	60	SB
						92703	E		GS	90	SM
						93001				120	SE
						93002					
						93003					
						94001					
						94002					
						94003					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	F1 Floor mounted, U bracket	S With Anti-Glare Shield X Without Anti-Glare Shield	WT Beam	E1 Elliptical beam 10° x 54°
CRI/CCT & Power	Control	IP	Body finish		
LED Load initial Lumen	C Built-in driver, non-dimmable D Built-in driver, DALI E Built-in driver, 1-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth		
2700°K	92701: 20 W/m 1950 lm/m 92702: 30 W/m 2700 lm/m 92703: 42 W/m 3600 lm/m				
3000°K	93001: 20 W/m 2150 lm/m 93002: 30 W/m 3000 lm/m 93003: 42 W/m 4000 lm/m				
4000°K	94001: 20 W/m 2350 lm/m 94002: 30 W/m 3200 lm/m 94003: 42 W/m 4250 lm/m				
Length	Wiring				
30 30 cm 60 60 cm 90 90 cm 120 120 cm	SI Side feeding, Individual SB Side feeding, Beginning SM Side feeding, Middle SE Side feeding, End				

