


LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

FLOOR MOUNTED, U BRACKET

The Lightway 5 outdoor grazing baffles is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP67 element benefits from specially-designed aluminum optics totally glare free from both the longitudinal and transversal sides of the profile, achieving a powerful effect while emphasizing rough-textured surfaces of great height.

- Best-in-class vertical surface grazing, Scallop-free lighting from zero start point of vertical surfaces
- Glare-free in both longitudinal and transversal sides
- 5 to 10cm from edge of fixture to surface of the wall depending on its height and surface.
- Use of continuous fixtures to within 10cm of side walls – Integrates with any architecture.
- IK08
- Ta: -10 to 40°C




Luminaire

Product Type: Grazer
Body Material: Extruded aluminium

Optics


Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles
Surface diffuser: No Diffuser




Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curve



Narrow Beam, 8° /
LOR: 35.5%



Narrow Beam, 15°
/ LOR: 30.0%

We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

FLOOR MOUNTED, U BRACKET

Code Index:

<u>L 5</u>	<u>O</u>	<u>F 1</u>	<u>X</u>	<u>---</u>	<u>---</u>	<u>-----</u>	<u>-</u>	<u>6 5</u>	<u>---</u>	<u>---</u>	<u>---</u>
Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
				GB	08	927P1	J		BS	30	SI
				GG	15	927P2	K		WS	60	SB
				GW		927P3	L		GS	90	SM
						930P1				120	SE
						930P2					
						930P3					
						940P1					
						940P2					
						940P3					
						927O1					
						927O2					
						927O3					
						930O1					
						930O2					
						930O3					
						940O1					
						940O2					
						940O3					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	F1 Floor mounted, U bracket	X Without Anti-Glare Shield	GB Black Grazing Baffles GG Gray Grazing Baffles GW White Grazing Baffles	08 Narrow Beam, 8° 15 Narrow Beam, 15°

CRI/CCT & Power	Control	IP	Body finish
<div>LED Load initial Lumen</div> <div>2700°K 927O1: 20 W/m 1950 lm/m 927O2: 30 W/m 2700 lm/m 927O3: 42 W/m 3600 lm/m 927P1: 20 W/m 1700 lm/m 927P2: 30 W/m 2250 lm/m 927P3: 42 W/m 3000 lm/m</div> <div>3000°K 930O1: 20 W/m 2150 lm/m 930O2: 30 W/m 3000 lm/m 930O3: 42 W/m 4000 lm/m 930P1: 20 W/m 1700 lm/m 930P2: 30 W/m 2400 lm/m 930P3: 42 W/m 3100 lm/m</div> <div>4000°K 940O1: 20 W/m 2350 lm/m 940O2: 30 W/m 3200 lm/m 940O3: 42 W/m 4250 lm/m 940P1: 20 W/m 1900 lm/m 940P2: 30 W/m 2550 lm/m 940P3: 42 W/m 3300 lm/m</div>	J Remote driver, non-dimmable K Remote driver, DALI L Remote driver, 1-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth

Length	Wiring
30 30 cm	SI Side feeding, Individual
60 60 cm	
90 90 cm	SB Side feeding, Beginning
120 120 cm	SM Side feeding, Middle
	SE Side feeding, End

We reserve the right to make technical changes without prior notice

