

# LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

## SHORT ROTATION ARM

The Lightway 5 outdoor grazing baffles is developed for maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP67 element benefits from specially-designed aluminum optics totally glare free from both the longitudinal and transversal sides of the profile, achieving a powerful effect while emphasizing rough-textured surfaces of great height.

- Best-in-class vertical surface grazing, Scallop-free lighting from zero start point of vertical surfaces
- Glare-free in both longitudinal and transversal sides
- 5 to 10cm from edge of fixture to surface of the wall depending on its height and surface.
- Use of continuous fixtures to within 10cm of side walls – Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



### Luminaire

**Product Type:** Grazer  
**Body Material:** Extruded aluminium


### Optics

**Optic Type:** UV stabilized TIR Lens  
**Glare Control Device:** Aluminium Anti-Glare Baffles  
**Surface diffuser:** No Diffuser


### Electrical equipment

**Mains Voltage:** 220-240 VAC 50/60 Hz  
**Control Gear Efficacy:** > 85%



### Polar Curve



Narrow Beam, 8° /  
LOR: 35.5%



Narrow Beam, 15°  
/ LOR: 30.0%



We reserve the right to make technical changes without prior notice

# LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

## SHORT ROTATION ARM

*We reserve the right to make technical changes without prior notice*



# LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

## SHORT ROTATION ARM

### Code Index:

<u>L 5</u>	<u>O</u>	<u>S 1</u>	<u>X</u>	<u>---</u>	<u>---</u>	<u>-----</u>	<u>-</u>	<u>6 5</u>	<u>---</u>	<u>---</u>	<u>---</u>
Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
				GB	08	927P1	J		BS	30	BI
				GG	15	927P2	K		WS	60	BB
				GW		927P3	L		GS	90	BM
						930P1				120	BE
						930P2					SI
						930P3					SB
						940P1					SM
						940P2					SE
						940P3					
						927O1					
						927O2					
						927O3					
						930O1					
						930O2					
						930O3					
						940O1					
						940O2					
						940O3					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	S1 Short rotation arm	X Without Anti-Glare Shield	GB Black Grazing Baffles GG Gray Grazing Baffles GW White Grazing Baffles	08 Narrow Beam, 8° 15 Narrow Beam, 15°
CRI/CCT & Power			Control	IP	Body finish
2700°K	LED Load	initial Lumen	J Remote driver, non-dimmable K Remote driver, DALI L Remote driver, 1-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth
	927O1:	20 W/m	1950 lm/m		
	927O2:	30 W/m	2700 lm/m		
	927O3:	42 W/m	3600 lm/m		
	927P1:	20 W/m	1700 lm/m		
	927P2:	30 W/m	2250 lm/m		
3000°K	927P3:	42 W/m	3000 lm/m		
	930O1:	20 W/m	2150 lm/m		
	930O2:	30 W/m	3000 lm/m		
	930O3:	42 W/m	4000 lm/m		
	930P1:	20 W/m	1700 lm/m		
	930P2:	30 W/m	2400 lm/m		
4000°K	930P3:	42 W/m	3100 lm/m		
	940O1:	20 W/m	2350 lm/m		
	940O2:	30 W/m	3200 lm/m		
	940O3:	42 W/m	4250 lm/m		
	940P1:	20 W/m	1900 lm/m		
	940P2:	30 W/m	2550 lm/m		
940P3:	42 W/m	3300 lm/m			

without prior notice



# LIGHTWAY 5 – OUTDOOR / GRAZING BAFFLES

## SHORT ROTATION ARM

### Length

**30** 30 cm  
**60** 60 cm  
**90** 90 cm  
**120** 120 cm

### Wiring

**BI** Bottom feeding,  
Individual  
**BB** Bottom feeding,  
Beginning  
**BM** Bottom feeding,  
Middle  
**BE** Bottom feeding, End  
**SI** Side feeding,  
Individual  
**SB** Side feeding,  
Beginning  
**SM** Side feeding, Middle  
**SE** Side feeding, End

We reserve the right to make technical changes without prior notice