

LIGHTWAY 3 / DOWNLIGHT

RECESSED WITH TRIM

The downlight dash is a modern concept of glare-free downlight with square distribution. This elegant luminaire is designed to host multiple reflectors of different beam angles, generating a perfect and flawless square distribution, ideal for diverse general lighting applications.

- Clean square light distribution from 25mm round aperture reflectors.
- The optimal beam angle over field angle ratio offers a highly-uniform horizontal surface
- Flexibility of mounting height with 3 beam angles
- Homogeneous color mixing within one reflector
- Glare-free illumination ($UGR < 0$) for narrow beam, ($UGR < 9$) for medium beam and ($UGR < 17$) for wide beam



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium


Optics

Optic Type: Special reflector of complex microfaceted surface
Glare Control Device: Cinco Cell Baffles
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curves





Narrow Beam, 36° /
LOR: 70.3%



Medium Beam, 50° /
LOR: 90.4%



Wide Beam, 60° /
LOR: 88.5%



LIGHTWAY 3 / DOWNLIGHT

RECESSED WITH TRIM

Code Index:

<u>L 3</u>	<u>I</u>	<u>R W</u>	<u>D D</u>	<u>—</u>	<u>—</u>	<u>— — — — —</u>	<u>—</u>	<u>2 0</u>	<u>—</u>	<u>I</u>	<u>—</u>
Family	Environment	Mounting	Application	Number of modules	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Layout	Length
				1	SN	927F1	J		BS		15
				2	SM	927F2	K		BT		30
				3	SW	927F3	L		WS		45
						930F1			WT		
						930F2			GS		
						930F3					
						940F1					
						940F2					
						940F3					
						9TWG1					
						9TWG2					
						9TWG3					

Family	Environment	Mounting	Application	Number of modules	Beam Angle
L3 Lightway 3	I Indoor	RW Recessed With Trim	DD Downlight Dash	1 1 Module 2 2 Modules 3 3 Modules	SN Narrow Beam, 36° SM Medium Beam, 50° SW Wide Beam, 60°

CRI/CCT & Power	Dimming	IP	Body finish
	J Remote driver, non dimmable K Remote driver, DALI L Remote driver, 1-10V	20 IP20	BS Black Smooth BT Black Textured WS White Smooth WT White Textured GS Gray Smooth
2700°K			
3000°K			
4000°K			
Tunable White			



LIGHTWAY 3 / DOWNLIGHT RECESSED WITH TRIM

Layout	Length
I I Shape	15 15 cm
	30 30 cm
	45 45 cm

