

LIGHTWAY 3 / DOWNLIGHT

SURFACE MOUNTED

The downlight dash is a modern concept of glare-free downlight with square distribution. This elegant luminaire is designed to host multiple reflectors of different beam angles, generating a perfect and flawless square distribution, ideal for diverse general lighting applications.

- Clean square light distribution from 25mm round aperture reflectors.
- The optimal beam angle over field angle ratio offers a highly-uniform horizontal surface
- Flexibility of mounting height with 3 beam angles
- Homogeneous color mixing within one reflector
- Glare-free illumination ($UGR < 0$) for narrow beam, ($UGR < 9$) for medium beam and ($UGR < 17$) for wide beam



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium




Optics

Optic Type: Special reflector of complex microfaceted surface
Glare Control Device: Cinco Cell Baffles
Surface diffuser: No Diffuser

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves



We reserve the right to make technical changes without prior notice

LIGHTWAY 3 / DOWNLIGHT

SURFACE MOUNTED

Code Index:

<u>L</u> <u>3</u>	<u>I</u>	<u>S</u> <u>M</u>	<u>D</u> <u>D</u>	<u> </u>	<u> </u> <u> </u>	<u> </u> <u> </u> <u> </u> <u> </u> <u> </u>	<u>C</u>	<u>2</u> <u>0</u>	<u> </u> <u> </u>	<u>I</u>	<u> </u> <u> </u>
Family	Environment	Mounting	Application	Number of modules	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Layout	Length
				2	SN	927F1			BS		30
				3	SM	927F2			BT		45
					SW	927F3			WS		
						930F1			WT		
						930F2			GS		
						930F3					
						940F1					
						940F2					
						940F3					

Family	Environment	Mounting	Application	Number of modules	Beam Angle
L3 Lightway 3	I Indoor	SM Surface Mounted	DD Downlight Dash	2 2 Modules 3 3 Modules	SN Narrow Beam, 36° SM Medium Beam, 50° SW Wide Beam, 60°

CRI/CCT & Power	Dimming	IP	Body finish
<div>2700°K</div> <div>927F1: 10 W 1000 lm 927F2: 15 W 1400 lm 927F3: 20 W 1800 lm 927F1: 15 W 1500 lm 927F2: 22.5 W 2100 lm 927F3: 30 W 2700 lm</div> <div>3000°K</div> <div>930F1: 10 W 1100 lm 930F2: 15 W 1500 lm 930F3: 20 W 1900 lm 930F1: 15 W 1650 lm 930F2: 22.5 W 2250 lm 930F3: 30 W 2850 lm</div> <div>4000°K</div> <div>940F1: 10 W 1100 lm 940F2: 15 W 1500 lm 940F3: 20 W 2000 lm 940F1: 15 W 1650 lm 940F2: 22.5 W 2250 lm 940F3: 30 W 3000 lm</div>	C Built-in driver, non dimmable	20 IP20	BS Black Smooth BT Black Textured WS White Smooth WT White Textured GS Gray Smooth

Layout	Length
I I Shape	30 30 cm 45 45 cm

We reserve the right to make technical changes without prior notice

