

LIGHTWAY 3 / DOWNLIGHT

RECESSED TRIMLESS

The downlight dash is a modern concept of glare-free downlight with square distribution. This elegant luminaire is designed to host multiple reflectors of different beam angles, generating a perfect and flawless square distribution, ideal for diverse general lighting applications.

- Clean square light distribution from 25mm round aperture reflectors.
- The optimal beam angle over field angle ratio offers a highly-uniform horizontal surface
- Flexibility of mounting height with 3 beam angles
- Homogeneous color mixing within one reflector
- Glare-free illumination ($UGR < 0$) for narrow beam, ($UGR < 9$) for medium beam and ($UGR < 17$) for wide beam



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium


Optics

Optic Type: Special reflector of complex microfaceted surface
Glare Control Device: Cinco Cell Baffles
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curves





Narrow Beam, 36° /
LOR: 70.3%



Medium Beam, 50° /
LOR: 90.4%



Wide Beam, 60° /
LOR: 88.5%



We reserve the right to make technical changes without prior notice

LIGHTWAY 3 / DOWNLIGHT

RECESSED TRIMLESS

Code Index:

<u>L 3</u>	<u>I</u>	<u>R T</u>	<u>D D</u>	<u>—</u>	<u>—</u>	<u>— — — — —</u>	<u>—</u>	<u>2 0</u>	<u>W S</u>	<u>I</u>	<u>—</u>
Family	Environment	Mounting	Application	Number of modules	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Layout	Length
				1	SN	927F1	J				15
				2	SM	927F2	K				30
				3	SW	927F3	L				45
						930F1					
						930F2					
						930F3					
						940F1					
						940F2					
						940F3					
						9TWG1					
						9TWG2					
						9TWG3					

Family	Environment	Mounting	Application	Number of modules	Beam Angle
L3 Lightway 3	I Indoor	RT Recessed Trimless	DD Downlight Dash	1 1 Module 2 2 Modules 3 3 Modules	SN Narrow Beam, 36° SM Medium Beam, 50° SW Wide Beam, 60°

CRI/CCT & Power	Dimming	IP	Body finish
	J Remote driver, non dimmable K Remote driver, DALI L Remote driver, 1-10V	20 IP20	WS White Smooth
			LED Load initial Lumen
2700°K			927F1: 5 W 500 lm 927F2: 7.5 W 700 lm 927F3: 10 W 900 lm 927F1: 10 W 1000 lm 927F2: 15 W 1400 lm 927F3: 20 W 1800 lm 927F1: 15 W 1500 lm 927F2: 22.5 W 2100 lm 927F3: 30 W 2700 lm
3000°K			930F1: 5 W 550 lm 930F2: 7.5 W 750 lm 930F3: 10 W 950 lm 930F1: 10 W 1100 lm 930F2: 15 W 1500 lm 930F3: 20 W 1900 lm 930F1: 15 W 1650 lm 930F2: 22.5 W 2250 lm 930F3: 30 W 2850 lm
4000°K			940F1: 5 W 550 lm 940F2: 7.5 W 750 lm 940F3: 10 W 1000 lm 940F1: 10 W 1100 lm 940F2: 15 W 1500 lm 940F3: 20 W 2000 lm 940F1: 15 W 1650 lm 940F2: 22.5 W 2250 lm 940F3: 30 W 3000 lm
Tunable White			9TWG1: 5 W 525 lm 9TWG2: 7.5 W 725 lm 9TWG3: 10 W 950 lm 9TWG1: 10 W 1050 lm 9TWG2: 15 W 1450 lm 9TWG3: 20 W 1900 lm 9TWG1: 15 W 1575 lm 9TWG2: 22.5 W 2175 lm 9TWG3: 30 W 2850 lm



LIGHTWAY 3 / DOWNLIGHT

RECESSED TRIMLESS

Layout	Length
I I Shape	15 15 cm
	30 30 cm
	45 45 cm

