LIGHTWAY 6 - OUTDOOR / CUT-OFF WASHER
INGROUND SHALLOW

The Lightway 6 Inground Cut-Off washer is developed for beautiful lighting in harsh environmental conditions. Made from extruded aluminum, this IP67 element marks a breakthrough in wall washing illumination as it offers different outputs with a flawless surface uniformity while blocking the backward and longitudinal light spill. It is glare- and light-pollution free.

- True wall wash distribution. Vertical light uniformity (1:4)
- Optimized cut-off: blocking the backward and longitudinal light spill (glare-free)
- Homogeneous color mixing within one reflector cell
- A minimum of 10 cm from side walls to prevent unwanted light spillage
- IK10

IP67

Luminaire

Product Type:	Washer
Body Material:	Extruded aluminium
Glass Cover:	Black Serigraphy

Optics

Optic Type:	Metallized Faceted Reflectors
Glare Control Device:	Micro Structured PMMA Lens
Surface diffuser:	Acrylic Micro Lenticular Structure Diffuser

Electrical equipment

Mains Voltage:	220-240 VAC 50/60 Hz
Control Gear Efficacy:	> 85%

Polar Curves

LOR: 58.85%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

LIGHTWAY 6 - OUTDOOR / CUT-OFF WASHER
INGROUND SHALLOW

Mounting Ratio

Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

LIGHTWAY 6 - OUTDOOR / CUT-OFF WASHER

INGROUND SHALLOW

Code Index:

L 6	O	I S	W O	X X	_ _ _ _ _	_	6 7	_ _	N	I	_ _ _	_
Family	**Environment**	**Mounting**	**Application**	**Beam Angle**	**CRI/CCT & Power**	**Dimming**	**IP**	**Body finish**	**Emergency**	**Layout**	**Length**	**Wiring**
					927M1	C		BS			30	I
					927M2	D		WS			60	M
					927M3	E		GS			90	
					930M1	F					120	
					930M2							
					930M3							
					940M1							
					940M2							
					940M3							

Family

L6 Lightway 6

Environment

O Outdoor

Mounting

IS Inground Shallow

Application

WO Cut-off Washer

Beam Angle

XX N/A

CRI/CCT & Power

		LED Load	initial Lumen
2700°K	**927M1:**	28 W/m	2250 lm/m
	927M2:	40 W/m	3050 lm/m
	927M3:	56 W/m	3950 lm/m
3000°K	**930M1:**	28 W/m	2300 lm/m
	930M2:	40 W/m	3150 lm/m
	930M3:	56 W/m	4150 lm/m
4000°K	**940M1:**	28 W/m	2500 lm/m
	940M2:	40 W/m	3400 lm/m
	940M3:	56 W/m	4450 lm/m

Dimming

C Built-in driver, non dimmable

D Built-in driver, DALI

E Built-in driver, 1-10V

F Built-in driver, Phase dim

IP

67 IP67

Body finish

BS Black Smooth

WS White Smooth

GS Gray Smooth

Emergency

N No Emergency

Layout

I I Shape

Length

30 30 cm

60 60 cm

90 90 cm

120 120 cm

Wiring

I Individual

M Beginning

M Middle

I End

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**

Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23