LIGHTWAY 6 / CUT-OFF WASHER
RECESSED TRIMLESS

The Lightway 6 Cut-Off Washer marks a breakthrough in wall washing illumination as it offers different outputs with a flawless surface uniformity while blocking the backward and longitudinal light spill. It is glare- and light-pollution free!
The Lightway 6 Cut-Off Washer is designed to be highly configurable and adaptable to a wide variety of commercial and architectural interior lighting applications.

- True wall wash distribution. Vertical light uniformity (1:4)
- Optimized cut-off: blocking the backward and longitudinal light spill (glare-free)
- Homogeneous color mixing within one reflector cell
- Setback ratio of 1:6
- Continuous rows or individual fixtures
- A minimum of 10 cm from side walls to prevent unwanted light spillage

GERMAN DESIGN AWARD SPECIAL 2017

IP20 LED

Luminaire

Product Type: Washer
Body Material: Extruded aluminium

Optics

Optic Type: Metallized Faceted Reflectors
Glare Control Device: Micro Structured PMMA Lens
Surface diffuser: Acrylic Micro Lenticular Structure Diffuser

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves

LOR: 70.76%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

LIGHTWAY 6 / CUT-OFF WASHER
RECESSED TRIMLESS

Mounting Ratio

Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

LIGHTWAY 6 / CUT-OFF WASHER
RECESSED TRIMLESS

Code Index:

L 6	I	R T	W O	X X	_ _ _ _ _	_	2 0	W S	N	I	_ _ _	_
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
					927M1	C					30	I
					927M2	D					60	B
					927M3	E					90	M
					930M1	F					120	E
					930M2						150	
					930M3						180	
					940M1						210	
					940M2						240	
					940M3						270	
					9TWD1						300	
					9TWD2							
					9TWD3							

Family

L6 Lightway 6

Environment

I Indoor

Mounting

RT Recessed Trimless

Application

WO Cut-off Washer

Beam Angle

XX N/A

CRI/CCT & Power

		LED Load	initial Lumen
2700°K	**927M1:**	28 W/m	2250 lm/m
	927M2:	40 W/m	3050 lm/m
	927M3:	56 W/m	3950 lm/m
3000°K	**930M1:**	28 W/m	2300 lm/m
	930M2:	40 W/m	3150 lm/m
	930M3:	56 W/m	4150 lm/m
4000°K	**940M1:**	28 W/m	2500 lm/m
	940M2:	40 W/m	3400 lm/m
	940M3:	56 W/m	4450 lm/m
Tunable White	**9TWD1:**	14 W/m	2400 lm/m
	9TWD2:	20 W/m	3250 lm/m
	9TWD3:	28 W/m	4200 lm/m

Dimming

C Built-in driver, non dimmable

D Built-in driver, DALI

E Built-in driver, 1-10V

F Built-in driver, Phase dim

IP

20 IP20

Body finish

WS White Smooth

Emergency

N No Emergency

Layout

I I Shape

Length

30 30 cm
60 60 cm
90 90 cm
120 120 cm
150 150 cm
180 180 cm
210 210 cm
240 240 cm
270 270 cm
300 300 cm

Wiring

I Individual
B Beginning
M Middle
E End

Notes

IP40 is applicable only for the individual items, however for the continuous runs it will be IP20.

We reserve the right to make technical changes without prior notice

VICE

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23