


LIGHTWAY 6 / ELLIPTICAL NARROW LENS

PENDANT DIRECT / INDIRECT

The Lightway 6 Direct/Indirect linear system offers numerous combinations of optics and output options. A well-lit ceiling improves the look of the workspace without having to compromise on the efficiency.

The elliptical narrow lens, for direct emission, provides homogeneous vertical surface grazing and works perfectly on high vertical surfaces.

- Wide lateral beam spread for high ceiling applications, over 4m height.
- Emphasizes contrast effects on textured surfaces
- 5 to 10cm from the edge of fixture to the surface of the wall
- Install to within 45cm of side walls to minimize spill



Luminaire

Product Type: Grazer
Body Material: Extruded aluminium

Optics

Optic Type: PMMA Linear Narrow Lens
Surface diffuser: Acrylic Frosted Extruded TIR Lens


Indirect Optic

Indirect Optic Type: PMMA Opal Lens

Electrical equipment


Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves




LOR: 82.3%

Indirect Polar Curves



LOR: 74.8%



We reserve the right to make technical changes without prior notice

LIGHTWAY 6 / ELLIPTICAL NARROW LENS

PENDANT DIRECT / INDIRECT

Mounting Ratio



100 to 150 mm

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

LIGHTWAY 6 / ELLIPTICAL NARROW LENS

PENDANT DIRECT / INDIRECT

Code Index:

<u>L</u> <u>6</u>	<u>I</u>	<u>P</u> <u>B</u>	<u>G</u> <u>L</u>	<u>X</u> <u>X</u>	_____	—	___	__	<u>N</u>	<u>I</u>	___	—	
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	CRI/CCT & Power	Indirect	Body finish	Emergency	Layout	Length	Wiring
					927L1	C	O1		BS			60	I
					927L2	D	O2		BT			90	B
					927L3	E	O3		WS			120	M
					927L4	F			WT			150	E
					927L5				GS			180	
					930L1							210	
					930L2							240	
					930L3							270	
					930L4							300	
					930L5								
					940L1								
					940L2								
					940L3								
					940L4								
					940L5								
					9TWT1								
					9TWT2								
					9TWT3								

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	I Indoor	PB Pendant Direct & Indirect	GL Elliptical Narrow Lens	XX N/A

CRI/CCT & Power	Dimming	CRI/CCT & Power Indirect	Body finish
<div>LED Load initial Lumen</div> <div>2700°K<div>927L1: 10 W/m 1200 lm/m</div><div>927L2: 15 W/m 1650 lm/m</div><div>927L3: 22 W/m 2150 lm/m</div><div>927L4: 30 W/m 3250 lm/m</div><div>927L5: 42 W/m 4300 lm/m</div></div> <div>3000°K<div>930L1: 10 W/m 1350 lm/m</div><div>930L2: 15 W/m 1900 lm/m</div><div>930L3: 22 W/m 2550 lm/m</div><div>930L4: 30 W/m 3800 lm/m</div><div>930L5: 42 W/m 5100 lm/m</div></div> <div>4000°K<div>940L1: 10 W/m 1450 lm/m</div><div>940L2: 15 W/m 2050 lm/m</div><div>940L3: 22 W/m 2700 lm/m</div><div>940L4: 30 W/m 4050 lm/m</div><div>940L5: 42 W/m 5400 lm/m</div></div> <div>Tunable White<div>9TWT1: 10 W/m 1350 lm/m</div><div>9TWT2: 15 W/m 1850 lm/m</div><div>9TWT3: 22 W/m 2450 lm/m</div></div>	<div>C Built-in driver, non dimmable</div> <div>D Built-in driver, DALI</div> <div>E Built-in driver, 1-10V</div> <div>F Built-in driver, Phase dim</div>	<div>LED Load initial Lumen</div> <div>2700°K<div>O1: Opal 10 W/m 1200 lm/m</div><div>O2: Opal 15 W/m 1650 lm/m</div><div>O3: Opal 22 W/m 2150 lm/m</div></div> <div>3000°K<div>O1: Opal 10 W/m 1350 lm/m</div><div>O2: Opal 15 W/m 1900 lm/m</div><div>O3: Opal 22 W/m 2550 lm/m</div></div> <div>4000°K<div>O1: Opal 10 W/m 1450 lm/m</div><div>O2: Opal 15 W/m 2050 lm/m</div><div>O3: Opal 22 W/m 2700 lm/m</div></div> <div>Tunable White<div>O1: Opal 10 W/m 1350 lm/m</div><div>O2: Opal 15 W/m 1850 lm/m</div><div>O3: Opal 22 W/m 2450 lm/m</div></div>	<div>BS Black Smooth</div> <div>BT Black Textured</div> <div>WS White Smooth</div> <div>WT White Textured</div> <div>GS Gray Smooth</div>

Emergency	Layout	Length	Wiring
N No Emergency	I I Shape	60 60 cm	I Individual
		90 90 cm	B Beginning
		120 120 cm	M Middle
		150 150 cm	E End
		180 180 cm	
		210 210 cm	
		240 240 cm	
		270 270 cm	
		300 300 cm	

