


# LIGHTWAY 6 / KICK REFLECTOR RECESSED WITH TRIM

The Lightway 6 Kick Reflector provides a smooth distribution of light over vertical surfaces and its reflector helps reduce the aperture apparent size, therefore its surface luminance.

Its aluminum optic with an integrated diffuser is specially designed to reduce glare and increase illuminance levels while providing a uniform light distribution.

- Exceptionally uniform wall washing, up to top of ceiling plane even when surface mounted
- Even wall illumination up to 6m
- Wide lateral illumination with excellent back light shielding
- Setback ratio of 1:5
- Continuous row mounting to within 45cm of side walls to minimize unwanted light spillage



## Luminaire

**Product Type:** Washer  
**Body Material:** Extruded aluminium



## Optics

**Optic Type:** Asymmetrical Reflector  
**Glare Control Device:** Kick Reflector  
**Surface diffuser:** Acrylic Non-glare Micro-diamond Prismatic Structure Lens

## Electrical equipment

**Mains Voltage:** 220-240 VAC 50/60 Hz  
**Control Gear Efficacy:** > 85%

## Polar Curves



*We reserve the right to make technical changes without prior notice*

# LIGHTWAY 6 / KICK REFLECTOR

## RECESSED WITH TRIM

### Mounting Ratio



Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

*We reserve the right to make technical changes without prior notice*

# LIGHTWAY 6 / KICK REFLECTOR

## RECESSED WITH TRIM

### Code Index:

<u>L 6</u>	<u>I</u>	<u>R W</u>	<u>W K</u>	<u>X X</u>	<u>    </u>	<u>2 0</u>	<u>    </u>	<u>N</u>	<u>I</u>	<u>    </u>	<u>    </u>	
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
					927L1	C		BS			30	I
					927L2	D		BT			60	B
					927L3	E		WS			90	M
					927L4	F		WT			120	E
					927L5			GS			150	
					930L1						180	
					930L2						210	
					930L3						240	
					930L4						270	
					930L5						300	
					940L1							
					940L2							
					940L3							
					940L4							
					940L5							
					9TWT1							
					9TWT2							
					9TWT3							

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	I Indoor	RW Recessed With Trim	WK Kick Reflector	XX N/A

CRI/CCT & Power	Dimming	IP	Body finish	Emergency
	C Built-in driver, non dimmable	20 IP20	BS Black Smooth	N No Emergency
	D Built-in driver, DALI		BT Black Textured	
	E Built-in driver, 1-10V		WS White Smooth	
	F Built-in driver, Phase dim		WT White Textured	
			GS Gray Smooth	

	LED Load	initial Lumen
2700°K	927L1: 10 W/m	1200 lm/m
	927L2: 15 W/m	1650 lm/m
	927L3: 22 W/m	2150 lm/m
	927L4: 30 W/m	3250 lm/m
	927L5: 42 W/m	4300 lm/m
3000°K	930L1: 10 W/m	1350 lm/m
	930L2: 15 W/m	1900 lm/m
	930L3: 22 W/m	2550 lm/m
	930L4: 30 W/m	3800 lm/m
	930L5: 42 W/m	5100 lm/m
4000°K	940L1: 10 W/m	1450 lm/m
	940L2: 15 W/m	2050 lm/m
	940L3: 22 W/m	2700 lm/m
	940L4: 30 W/m	4050 lm/m
	940L5: 42 W/m	5400 lm/m
Tunable White	9TWT1: 10 W/m	1350 lm/m
	9TWT2: 15 W/m	1850 lm/m
	9TWT3: 22 W/m	2450 lm/m



# LIGHTWAY 6 / KICK REFLECTOR

## RECESSED WITH TRIM

Layout	Length	Wiring
I I Shape	<b>30</b> 30 cm	<b>I</b> Individual
	<b>60</b> 60 cm	<b>B</b> Beginning
	<b>90</b> 90 cm	<b>M</b> Middle
	<b>120</b> 120 cm	<b>E</b> End
	<b>150</b> 150 cm	
	<b>180</b> 180 cm	
	<b>210</b> 210 cm	
	<b>240</b> 240 cm	
	<b>270</b> 270 cm	
	<b>300</b> 300 cm	

### Notes

IP40 is applicable only for the individual items, however for the continuous runs it will be IP20.