

LIGHTWAY 6 / KICK REFLECTOR

PENDANT DIRECT

The Lightway 6 Kick Reflector provides a smooth distribution of light over vertical surfaces and its reflector helps reduce the aperture apparent size, therefore its surface luminance.

Its aluminum optic with an integrated diffuser is specially designed to reduce glare and increase illuminance levels while providing a uniform light distribution.

- Exceptionally uniform wall washing, up to top of ceiling plane even when surface mounted
- Even wall illumination up to 6m
- Wide lateral illumination with excellent back light shielding
- Setback ratio of 1:5
- Continuous row mounting to within 45cm of side walls to minimize unwanted light spillage



Luminaire

Product Type: Washer
Body Material: Extruded aluminium


Optics

Optic Type: Asymmetrical Reflector
Glare Control Device: Kick Reflector
Surface diffuser: Acrylic Non-glare Micro-diamond Prismatic Structure Lens


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves



LOR: 58.7%




We reserve the right to make technical changes without prior notice

LIGHTWAY 6 / KICK REFLECTOR

PENDANT DIRECT

Mounting Ratio



Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

LIGHTWAY 6 / KICK REFLECTOR

PENDANT DIRECT

Code Index:

L 6	I	P D	W K	X X	— — — — —	—	2 0	— —	N	I	— — —	—
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
					927L1	C		BS			30	I
					927L2	D		BT			60	B
					927L3	E		WS			90	M
					927L4	F		WT			120	E
					927L5			GS			150	
					930L1						180	
					930L2						210	
					930L3						240	
					930L4						270	
					930L5						300	
					940L1							
					940L2							
					940L3							
					940L4							
					940L5							
					9TWT1							
					9TWT2							
					9TWT3							

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	I Indoor	PD Pendant Direct	WK Kick Reflector	XX N/A

CRI/CCT & Power			Dimming	IP	Body finish	Emergency
2700°K	LED Load	initial Lumen	C Built-in driver, non dimmable D Built-in driver, DALI E Built-in driver, 1-10V F Built-in driver, Phase dim	20 IP20	BS Black Smooth	N No Emergency
	927L1:	10 W/m 1200 lm/m			BT Black Textured	
	927L2:	15 W/m 1650 lm/m			WS White Smooth	
	927L3:	22 W/m 2150 lm/m			WT White Textured	
	927L4:	30 W/m 3250 lm/m			GS Gray Smooth	
3000°K	927L5:	42 W/m 4300 lm/m				
	930L1:	10 W/m 1350 lm/m				
	930L2:	15 W/m 1900 lm/m				
	930L3:	22 W/m 2550 lm/m				
	930L4:	30 W/m 3800 lm/m				
4000°K	930L5:	42 W/m 5100 lm/m				
	940L1:	10 W/m 1450 lm/m				
	940L2:	15 W/m 2050 lm/m				
	940L3:	22 W/m 2700 lm/m				
	940L4:	30 W/m 4050 lm/m				
Tunable White	940L5:	42 W/m 5400 lm/m				
	9TWT1:	10 W/m 1350 lm/m				
	9TWT2:	15 W/m 1850 lm/m				
	9TWT3:	22 W/m 2450 lm/m				



LIGHTWAY 6 / KICK REFLECTOR

PENDANT DIRECT

Layout	Length	Wiring
I I Shape	30 30 cm	I Individual
	60 60 cm	B Beginning
	90 90 cm	M Middle
	120 120 cm	E End
	150 150 cm	
	180 180 cm	
	210 210 cm	
	240 240 cm	
	270 270 cm	
	300 300 cm	

Notes

IP40 is applicable only for the individual items, however for the continuous runs it will be IP20.