


LIGHTWAY 6 – OUTDOOR / GRAZING BAFFLES

INGROUND SHALLOW

The Lightway 6 Inground grazing baffles is developed for beautiful lighting in harsh environmental conditions. Made from extruded aluminum, this IP67 element benefits from specially-designed aluminum optics totally glare free from both the longitudinal and transversal sides of the profile, achieving a powerful effect while emphasizing rough-textured surfaces of great height.

- Best-in-class vertical surface grazing, Scallop-free lighting from zero start point of vertical surfaces
- Glare-free in both longitudinal and transversal sides
- 5 to 10cm from edge of fixture to surface of the wall depending on its height and surface. Use of continuous fixtures to within 10cm of side walls
- IK10



light
MIDDLE EAST
AWARDS
2016



reddot award 2017
winner



Luminaire

Product Type: Grazer
Body Material: Extruded aluminium
Glass Cover: Black Serigraphy


Optics

Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles and Linear Glare Shield
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curves



Narrow Beam, 8° /
LOR: 26.3%



Narrow Beam, 16° /
LOR: 25.7%




We reserve the right to make technical changes without prior notice

LIGHTWAY 6 – OUTDOOR / GRAZING BAFFLES

INGROUND SHALLOW

Mounting Ratio



Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

LIGHTWAY 6 – OUTDOOR / GRAZING BAFFLES

INGROUND SHALLOW

Code Index:

<u>L</u> <u>6</u>	<u>O</u>	<u>I</u> <u>S</u>	<u> </u>	<u> </u>	<u> </u> <u> </u> <u> </u>	<u> </u>	<u>6</u> <u>7</u>	<u> </u>	<u>N</u>	<u>I</u>	<u> </u> <u> </u>	<u> </u>
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
			GB	08	927P1	C		BS			30	I
			GG	16	927P2	D		WS			60	M
			GW		927P3	E		GS			90	
					930P1	F					120	
					930P2							
					930P3							
					940P1							
					940P2							
					940P3							

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	O Outdoor	IS Inground Shallow	GB Black Grazing Baffles GG Gray Grazing Baffles GW White Grazing Baffles	08 Narrow Beam, 8° 16 Narrow Beam, 16°
CRI/CCT & Power	Dimming	IP	Body finish	Emergency
LED Load initial Lumen	C Built-in driver, non dimmable	67 IP67	BS Black Smooth	N No Emergency
2700°K 927P1: 20 W/m 1700 lm/m 927P2: 30 W/m 2250 lm/m 927P3: 42 W/m 3000 lm/m	D Built-in driver, DALI		WS White Smooth	
3000°K 930P1: 20 W/m 1700 lm/m 930P2: 30 W/m 2400 lm/m 930P3: 42 W/m 3100 lm/m	E Built-in driver, 1-10V		GS Gray Smooth	
4000°K 940P1: 20 W/m 1900 lm/m 940P2: 30 W/m 2550 lm/m 940P3: 42 W/m 3300 lm/m	F Built-in driver, Phase dim			

Layout	Length	Wiring
I I Shape	30 30 cm 60 60 cm 90 90 cm 120 120 cm	I Individual M Beginning M Middle I End

