

LIGHTWAY 6 / SYMMETRICAL BAFFLES SURFACE MOUNTED

The Lightway 6 Symmetrical Baffles is designed as a modern replacement for the traditional baffled fluorescent linear fixtures.

The baffles offer excellent glare control and are compatible with a wide array of beam angles.

The specially-designed aluminum optics with high-power LEDs generate a powerful overall lighting effect.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptical
- Excellent glare control and visual cutoff. Transversal & longitudinal shielding angle (45°)
- Delivers High levels of light
- Endless baffle tray colors and finish options for a decorative look



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium


Optics

Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%


Polar Curves



Medium Beam, 30° /
LOR: 85.6%




Wide Beam, 45° /
LOR: 76.8%



Elliptical beam 15° x 36° /
LOR: 88%



reddot award 2017
winner



LIGHTWAY 6 / SYMMETRICAL BAFFLES

SURFACE MOUNTED

Code Index:

L 6	I	S M	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
			AB	30	92701	C		BS			30	I
			AG	45	92702	D		BT			60	B
			AW	E2	92703	E		WS			90	M
					93001	F		WT			120	E
					93002			GS			150	
					93003						180	
					94001						210	
					94002						240	
					94003						270	
											300	

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	I Indoor	SM Surface Mounted	AB Black Symmetrical Baffles AG Gray Symmetrical Baffles AW White Symmetrical Baffles	30 Medium Beam, 30° 45 Wide Beam, 45° E2 Elliptical beam 15° x 36°
CRI/CCT & Power	Dimming	IP	Body finish	Emergency
2700°K 92701: 20 W/m 1950 lm/m 92702: 30 W/m 2700 lm/m 92703: 42 W/m 3600 lm/m 3000°K 93001: 20 W/m 2150 lm/m 93002: 30 W/m 3000 lm/m 93003: 42 W/m 4000 lm/m 4000°K 94001: 20 W/m 2350 lm/m 94002: 30 W/m 3200 lm/m 94003: 42 W/m 4250 lm/m	C Built-in driver, non dimmable D Built-in driver, DALI E Built-in driver, 1-10V F Built-in driver, Phase dim	20 IP20	BS Black Smooth BT Black Textured WS White Smooth WT White Textured GS Gray Smooth	N No Emergency

Layout	Length	Wiring
I I Shape	30 30 cm 60 60 cm 90 90 cm 120 120 cm 150 150 cm 180 180 cm 210 210 cm 240 240 cm 270 270 cm 300 300 cm	I Individual B Beginning M Middle E End

We reserve the right to make technical changes without prior notice

