

LIGHTWAY 6 / ASYMMETRICAL LENS RECESSED TRIMLESS

The Lightway 6 Asymmetrical Linear Lens provides homogeneous distribution of light over vertical surfaces. It achieves a very high output, making it ideal for high-ceiling lighting applications. The light distribution pattern is optimized for use in a wide variety of applications such as retail shelves and display lighting.

- The flush lens delivers the best wall uniformity. Vertical light uniformity (1:3)
- High output, ideal for vertical surfaces (over 4 meters high lighting applications)
- Wide lateral illumination with minimal cut-off
- Setback ratio (1:4 to 1:6)
- 45cm of side walls to minimize unwanted light spillage



Luminaire

Product Type: Washer
Body Material: Extruded aluminium


Optics

Optic Type: PMMA Asymmetrical Linear Lens
Surface diffuser: Acrylic Frosted Extruded TIR Lens


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves




LOR: 81.1%



We reserve the right to make technical changes without prior notice

LIGHTWAY 6 / ASYMMETRICAL LENS RECESSED TRIMLESS

Mounting Ratio



Height/6 to Height/5

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

LIGHTWAY 6 / ASYMMETRICAL LENS

RECESSED TRIMLESS

Code Index:

L 6	I	R T	W L	X X			2 0	W S	N	I		
Family	Environment	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length	Wiring
					927L1	C					30	I
					927L2	D					60	B
					927L3	E					90	M
					927L4	F					120	E
					927L5						150	
					930L1						180	
					930L2						210	
					930L3						240	
					930L4						270	
					930L5						300	
					940L1							
					940L2							
					940L3							
					940L4							
					940L5							
					9TWT1							
					9TWT2							
					9TWT3							

Family	Environment	Mounting	Application	Beam Angle
L6 Lightway 6	I Indoor	RT Recessed Trimless	WL Asymmetrical Lens	XX N/A

CRI/CCT & Power	Dimming	IP	Body finish	Emergency
	C Built-in driver, non dimmable	20 IP20	WS White Smooth	N No Emergency
	D Built-in driver, DALI			
	E Built-in driver, 1-10V			
	F Built-in driver, Phase dim			
2700°K				
3000°K				
4000°K				
Tunable White				



LIGHTWAY 6 / ASYMMETRICAL LENS

RECESSED TRIMLESS

Layout	Length	Wiring
I I Shape	30 30 cm	I Individual
	60 60 cm	B Beginning
	90 90 cm	M Middle
	120 120 cm	E End
	150 150 cm	
	180 180 cm	
	210 210 cm	
	240 240 cm	
	270 270 cm	
	300 300 cm	

Notes

IP40 is applicable only for the individual items, however for the continuous runs it will be IP20.

We reserve the right to make technical changes without prior notice