ZINC UNO / WASHER
SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky floodlights and spotlights. The Uno showcases a compact high-performance tool that can host a multitude of optics which allows this product to be used in all kinds of Architectural and urban applications.
Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.
This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

Product Features:
- Homogeneous color mixing within one reflector
- IP 66
- Different optics serving different lighting application:
  - o Wall washer
  - o Wall grazer
  - o Flood light

IP66 CE LED

Luminaire

Product Type: Washer
Body Material: Extruded aluminium

Optics

Optic Type: Metallized Faceted Reflectors
Glare Control Device: Micro Structured PMMA Lens
Surface diffuser: Acrylic Micro Lenticular Structure Diffuser

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves

LOR: 61%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / WASHER
SURFACE MOUNTED

Mounting Ratio

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / WASHER
SURFACE MOUNTED

Code Index:

Z 3	U	O S M	W O	X X	_ _ _ _ _	_	6 6	_ _	N	I	0 8
Family	Product	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length
					927M1	C		BS			
					927M2	J		WS			
					927M3	K		GS			
					930M1	L					
					930M2	M					
					930M3						
					940M1						
					940M2						
					940M3						
					9TWD1						
					9TWD2						
					9TWD3						
					9WDD1						
					9WDD2						
					9WDD3						

Family

Z3
Zinc

Product

U Uno

Mounting

OSM Surface Mounted

Application

WO Cut-off Washer

Beam Angle

XX N/A

CRI/CCT & Power

		LED Load	initial Lumen
2700°K	**927M1:**	2 W	165 lm
	927M2:	3 W	220 lm
	927M3:	4 W	300 lm
3000°K	**930M1:**	2 W	170 lm
	930M2:	3 W	230 lm
	930M3:	4 W	300 lm
4000°K	**940M1:**	2 W	180 lm
	940M2:	3 W	250 lm
	940M3:	4 W	325 lm
Tunable White	**9TWD1:**	1 W	175 lm
	9TWD2:	1.5 W	235 lm
	9TWD3:	2 W	315 lm
Warm Dimming	**9WDD1:**	1 W	170 lm
	9WDD2:	1.5 W	230 lm
	9WDD3:	2 W	300 lm

Dimming

C Built-in driver, non dimmable

J Remote driver, non dimmable

K Remote driver, DALI

L Remote driver, 1-10V

M Remote driver, Phase dim

IP

66 IP66

Body finish

BS Black Smooth

WS White Smooth

GS Gray Smooth

Emergency

N No Emergency

Layout

I I Shape

Length

08 8 cm

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23