ZINC UNO / GRAZER
SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky floodlights and spotlights. The Uno showcases a compact high-performance tool that can host a multitude of optics which allows this product to be used in all kinds of Architectural and urban applications.
Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.
This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

Product Features:
- Homogeneous color mixing within one reflector
- IP 66
- Different optics serving different lighting application:
  - o Wall washer
  - o Wall grazer
  - o Flood light

IP66 LED

Luminaire

Product Type: Grazer
Body Material: Extruded aluminium

Optics

Optic Type: UV stabilized TIR Lens
Surface diffuser: No Diffuser

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curves

Narrow Beam, 8° / LOR: 83%

Narrow Beam, 16° / LOR: 72%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / GRAZER
SURFACE MOUNTED

Mounting Ratio

Setback from the wall is defined by wall texture and height. Consult factory for optimal setback according to your project conditions.

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / GRAZER
SURFACE MOUNTED

Code Index:

Z 3	U	O S M	G T	_ _	_ _ _ _ _	_	6 6	_ _	N	I	0 8
Family	Product	Mounting	Application	Beam Angle	CRI/CCT & Power	Dimming	IP	Body finish	Emergency	Layout	Length
				08	927P1	C		BS			
				16	927P2	J		WS			
					927P3	K		GS			
					930P1	L					
					930P2	M					
					930P3						
					940P1						
					940P2						
					940P3						

Family

Z3 Zinc

Product

U Uno

Mounting

OSM Surface Mounted

Application

GT Beam

Beam Angle

08 Narrow Beam, 8°
16 Narrow Beam, 16°

CRI/CCT & Power

		LED Load	initial Lumen
2700°K	**927P1:**	1 W	80 lm
	927P2:	1.5 W	110 lm
	927P3:	2 W	150 lm
3000°K	**930P1:**	1 W	85 lm
	930P2:	1.5 W	115 lm
	930P3:	2 W	150 lm
4000°K	**940P1:**	1 W	90 lm
	940P2:	1.5 W	125 lm
	940P3:	2 W	160 lm

Dimming

C Built-in driver, non dimmable
J Remote driver, non dimmable
K Remote driver, DALI
L Remote driver, 1-10V
M Remote driver, Phase dim

IP

66 IP66

Body finish

BS Black Smooth
WS White Smooth
GS Gray Smooth

Emergency

N No Emergency

Layout

I I Shape

Length

08 8 cm

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23