ZINC UNO / FLOODLIGHT
SURFACE MOUNTED

Zinc is designed to contrast with the existing blocky floodlights and spotlights. The Uno showcases a compact high-performance tool that can host a multitude of optics which allows this product to be used in all kinds of Architectural and urban applications.
Zinc line leaves minimal physical impact while blending smoothly within its environment. In spite the compact design Zinc luminaires can host different optics to serve different lighting situations.
This product can be mounted vertically or horizontally and has a tilt adjustment up to 90°, allowing designers to illuminate horizontal, sloped, and vertical surfaces alike.

Product Features:
- Homogeneous color mixing within one reflector
- IP 66
- Different optics serving different lighting application:
  - o Wall washer
  - o Wall grazer
  - o Flood light

IP66

Luminaire

Product Type:	Ambient
Body Material:	Extruded aluminium

Optics

Optic Type:	UV stabilized TIR Lens
Surface diffuser:	No Diffuser

Electrical equipment

Mains Voltage:	220-240 VAC 50/60 Hz
Control Gear Efficacy:	> 85%

Polar Curves

Medium Beam, 30° /
LOR: 82%

Wide Beam, 45° /
LOR: 65.4%

Elliptical beam 10° x 54° /
LOR: 72%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / FLOODLIGHT
SURFACE MOUNTED

Elliptical beam 15° x 36° /
LOR: 78%

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**
Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23

ZINC / FLOODLIGHT
SURFACE MOUNTED

Code Index:

Z 3	U	O S M	A T	_ _	_ _ _ _ _	_	6 6	_ _	N	I	0 8
Family	**Product**	**Mounting**	**Application**	**Beam Angle**	**CRI/CCT & Power**	**Dimming**	**IP**	**Body finish**	**Emergency**	**Layout**	**Length**
				30	92701	C		BS			
				45	92702	J		WS			
				E1	92703	K		GS			
				E2	93001	L					
					93002	M					
					93003						
					94001						
					94002						
					94003						

Family

Z3 Zinc

Product

U Uno

Mounting

OSM Surface Mounted

Application

AT Floodlight, Beam

Beam Angle

30 Medium Beam, 30°

45 Wide Beam, 45°

E1 Elliptical beam 10° x 54°

E2 Elliptical beam 15° x 36°

CRI/CCT & Power

		LED Load	initial Lumen
2700°K	**92701:**	1 W	100 lm
	92702:	1.5 W	135 lm
	92703:	2 W	175 lm
3000°K	**93001:**	1 W	110 lm
	93002:	1.5 W	150 lm
	93003:	2 W	200 lm
4000°K	**94001:**	1 W	115 lm
	94002:	1.5 W	155 lm
	94003:	2 W	210 lm

Dimming

C Built-in driver, non dimmable

J Remote driver, non dimmable

K Remote driver, DALI

L Remote driver, 1-10V

M Remote driver, Phase dim

IP

66 IP66

Body finish

BS Black Smooth

WS White Smooth

GS Gray Smooth

Emergency

N No Emergency

Layout

I I Shape

Length

08 8 cm

We reserve the right to make technical changes without prior notice

projects@vicelighting.com - **www.vicelighting.com**

Lebanon 11-0125-Beirut +961 1 486311 - **France** 75012 Paris +33 06 75 32 73 23