


CONO PD

664-001000323660


CONO SUSPENSION made of aluminium, black matt, similar to RAL 9005, anti-glare LF0 lens due to microfaceted structure beam 55°, light output direct, UGR <16, with converter, max. 350mA, cable black, soft-touch, adapter/ceiling base black, pendant length 1500mm, IP20



DRAWING



LIGHT DISTRIBUTION CURVE



TECHNICAL DETAILS

System perform. [W]	6
Bulb type	LED
Luminous flux [lm]	270
Current sec. [mA]	350
Colour temp. [K]	2700K
CRI	>90
UGR	<16
Optics	LF0 lens
Designer	March Gut
Light output	direct
Beam angle [°]	55°
Voltage [V]	220-240V 50/60Hz
Material	aluminium

Length [mm]	140
Height [mm]	131,5
Pendant length [mm]	1500
Diameter [mm]	100
IP protection class	IP20
Voltage class	protection cl. II
Net weight [kg]	0,6326

Color	black matt
RAL	9005
Color adapter	black
Electric wire	black, soft-touch
EAN-Number	9008905777028
Lifetime [h]	50 000 L80 B10
Energy efficiency cl.	A++-A
No. of luminaires B16A	50

The values are rated values. Power and luminous flux are initially subject to a tolerance of +/- 10%. Colour temperature tolerance: +/- 150 K. The values apply to an ambient temperature of 25°C unless otherwise specified.