



REF.


Per ogni voce selezionare l'opzione scelta
For each item select the chosen option

1

.FRAME CEILING

FOLIO®

	product type	sizes	LED position	CCT	al finish	op finish	fixing		warranty	dimmm.	LED type	IP Rating	Indirect Light	Track System	Spot. Mate	fabric
Q.ty		15 25														



W 150
1500 x 2500 mm


W 5.90
59.05 x 98.42 in

Altre dimensioni disponibili.
Custom size available.

CERTIFICATIONS



APPLICATIONS



TECHNICAL DESCRIPTION

FRAME è la serie di prodotti Folio a cornice rettangolare e quadrata con dimensione massima **2000 x 3000 mm**. Omogeneità luminosa garantita dal diffusore opale con spessore 10 mm e dalla lastra interna in metacrilato incisa a laser con tecnologia edge lighting. Protezione esterna con scocca in alluminio per favorire la rigidità e la dissipazione del calore. LED Nichia ad alta efficienza energetica, dimmerabili 0-10 V, DALI, DMX o Casambi. Disponibile nelle versioni con alimentatore remoto o con alimentatore integrato.

FRAME is the series of Folio products with rectangular and square frames with a maximum size of 2000 x 3000 mm. Homogeneous luminosity is guaranteed by the opal diffuser with a thickness of 10 mm. The internal methacrylate plate is laser engraved with lighting edge technology. The external protection made of an aluminum shell favours rigidity and heat dissipation. The Nichia LEDs with high energy efficiency, are dimmable 0-10 V, DALI, DMX or Casambi. Available either with remote or integrated power supply.



REF.




Per ogni voce selezionare l'opzione scelta
For each item select the chosen option

2

.FRAME CEILING

FOLIO®

	product type	sizes	LED position	CCT	al finish	op finish	fixing		warranty	dim.	LED type	IP Rating	Indirect Light	Track System	Spot. Mate	fabric
Q.ty		15 25														



QUANTITÀ
QUANTITIES



W 150
1500 x 2500 mm

W 5.90

59.05 x 98.42 in



PHYSICAL SPECS.

Tipologia di prodotto:
Product type:



F.A Versione con **alimentazione remota**
(alimentatore non incluso)
Remote power supply version
(power supply not included)



F.B Versione con **alimentazione integrata**
(alimentatore non incluso)
Integrated power supply version
(power supply not included)

Spessore:
Thickness:

F.A 44 mm
1.73 in

Spessore:
Thickness:

F.B 49 mm
1.92 in

Peso:
Weight:

60 kg
132.27 lb

Materiali:
Materials:

Alluminio - Metacrilato
Aluminum - Methacrylate

Dimensioni:
Sizes:

W 150 mm
5.90 in
H 1500 mm
59.05 in
L 2500 mm
98.42 in

GENERAL SPECS.

Installazione:
Fixing:



C A soffitto
Ceiling

Ambiente di utilizzo:
Environment of use:

Interno
Indoor

Durata LED:
LED lifespan:

L90 > 60.000 ore a 50° Celsius
L90 > 60.000 hours at 50° Celsius

Blue light risk group:
Blue light risk group:

EXEMPT UNLIMITED (200 mm)
EXEMPT UNLIMITED (7.87 in)

Garanzia:
Warranty:



2Y 2 anni
2 years



5Y Su richiesta estensione fino a 5 anni
On request extension up to 5 years

FINISHES

Finiture alluminio:
Aluminum finishes:



W bianco
white



B nero
black



S speciale (verniciatura o ossidazione)
special (liquid painting or oxidation)

Finiture opale:
Opal finishes:



M opaco
matte



G lucido
gloss



OM opale fresato
opal milling



OS opale inciso laser
opal sculpture



OP opale + stampa
opal + print



OA opale + stampa lucida (Folio Art)
opal + glossy print (Folio Art)



REF.

Per ogni voce selezionare l'opzione scelta
For each item select the chosen option

3

.FRAME CEILING

FOLIO®

	product type	sizes	LED position	CCT	al finish	op finish	fixing		warranty	dim.	LED type	IP Rating	Indirect Light	Track System	Spot. Mate	fabric
Q.ty		15 25														

ELECTRICAL SPECS.

Voltaggio:

Voltage:

Driver - alimentatore:

Driver - power supply:

Dimmerabilità:

Dimmability:

☐

010

0-10 V

☐

DA

DALI

☐

DM

DMX

☐

CA

Casambi

LED

Tipologia LED:

LED type:

☐

N

NICHIA 757 R9050

☐

O

Nichia Optisolis™ (su richiesta)
Nichia Optisolis™ (on request)☐

V

Nichia Vitasolis™ (su richiesta)
Nichia Vitasolis™ (on request)

Posizione LED:

LED position:

☐

P1

Perimetro esterno

External perimeter

☐

P2

Perimetro esterno ed interno

External and internal perimeters

Consumo:

Consumption:

P1

200 W

P2

370 W

Flusso luminoso output:

Luminous flux output:

P1

5324 lm

P2

9680 lm

Indice di resa cromatica:

Color rendering index:

N

Standard:
CRI = Ra min. 90 - R9 min. 50

O

Su richiesta Ra = 100
(Nichia Optisolis™)
On request Ra = 100
(Nichia Optisolis™)

Grado di protezione:

IP rating:

☐

40

Standard:

IP40

☐

65

IP65 (su richiesta)
IP65 (on request)☐

DL

Damp Location (su richiesta)
Damp Location (on request)

Temperatura colore LED:

LED color temp. (CCT):

☐

27

2700 K

☐

30

3000 K

☐

35

3500 K

☐

40

4000 K

☐

57

5700 K

☐

TW

Tunable White (2700 K - 5700 K)

☐

RQ

Su richiesta 2000K, 2200K, 2500K,
5000K, 6500K, RGB, RGBW and
RGBTW
On request 2000K, 2200K, 2500K,
5000K, 6500K, RGB, RGBW and
RGBTW

UGR

Indici di riflessione:

Reflectance indexes:

X = 4H, Y = 8H, S = 0,25H

70/ 50/ 20

UGR trasversale:

UGR crosswise:

< 19


UGR longitudinale:

UGR endwise:

< 19

POLAR DIAGRAM

[cd/klm]





REF.

Per ogni voce selezionare l'opzione scelta
For each item select the chosen option

4

.FRAME CEILING

FOLIO®

	product type	sizes	LED position	CCT	al finish	op finish	fixing		warranty	dimm.	LED type	IP Rating	Indirect Light	Track System	Spot. Mate	fabric
Q.ty		15 25														

LIGHTING ACCESSORIES

Folio Indirect Light:



<input type="checkbox"/>	27	2700 K
<input type="checkbox"/>	30	3000K
<input type="checkbox"/>	35	3500K
<input type="checkbox"/>	40	4000K
<input type="checkbox"/>	57	5700K
<input type="checkbox"/>	RQ	Su richiesta 2000K, 2200K, 2500K, 6500K, RGB and RGBW On request 2000K, 2200K, 2500K, 6500K, RGB and RGBW

FOLIO LINEAR		
<input type="checkbox"/>	TINY	TINY
<input type="checkbox"/>	TY45	TINY 45
<input type="checkbox"/>	STK	STOCKY

<input type="checkbox"/>	30	3000K
<input type="checkbox"/>	40	4000K
<input type="checkbox"/>	57	5700K
<input type="checkbox"/>	TW	Tunable White (2700 K - 5700 K)
<input type="checkbox"/>	R	RGB
<input type="checkbox"/>	RQ	Su richiesta 2000K, 2200K, 2500K, 2700K, 3500K and 6500K On request 2000K, 2200K, 2500K, 2700K, 3500K and 6500K

Tessuto fonoassorbente:
Sound-absorbing fabric:

<input type="checkbox"/>	SA	Colori su richiesta Colors on request
--------------------------	----	--

Folio Track System®:



Folio Spot.Mate®:



<input type="checkbox"/>	26.a	Pico 26.a	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	40.a	Micro 40.a	Qty.	<input type="checkbox"/>
Lungh. fino a 3000 mm Length up to 118.11 in				

<input type="checkbox"/>	DQ	Domino Quad	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	DL	Domino Linear	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	26.t	Pico 26.t	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	26.a	Pico 26.a	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	40.t	Micro 40.t	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	40.a	Micro 40.a	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	62.a	Mini 62.a	Qty.	<input type="checkbox"/>
<input type="checkbox"/>	77.a	Midi 77.a	Qty.	<input type="checkbox"/>

KEY TO SYMBOLS

Folio Indirect Light:



Folio Track System®:



Folio Spot.Mate®:

