

LIGHTWAY 5 – OUTDOOR / OPAL

SHORT ROTATION ARM

The Lightway 5 outdoor opal is developed for homogenous lighting in harsh environments. This IP65 element benefits from a wide variety of outputs. The diffuser offers powerful lighting and excellent light transmission with high diffusion.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Superior optical transmission with no visible LED hotspots
- Wide, even levels of illumination
- High angle distribution to illuminate vertical & horizontal surfaces
- Great color mixing capability
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium





Optics

Optic Type: PMMA Opal Lens
Surface diffuser: Acrylic Opal Diffusing Lens

Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curve





We reserve the right to make technical changes without prior notice



LIGHTWAY 5 – OUTDOOR / OPAL

SHORT ROTATION ARM



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / OPAL

SHORT ROTATION ARM

Code Index:

<u>L 5</u>	<u>O</u>	<u>S 1</u>	<u>—</u>	<u>A O</u>	<u>X X</u>	<u>— — — — —</u>	<u>—</u>	<u>6 5</u>	<u>— —</u>	<u>— — —</u>	<u>— —</u>	
Family	Environment	Mounting	Glare Control	Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
			S				927L1	C		BS	30	BI
			X				927L2	D		WS	60	BB
							927L3	E		GS	90	BM
							927L4				120	BE
							927L5					SI
							930L1					SB
							930L2					SM
							930L3					SE
							930L4					
							930L5					
							940L1					
							940L2					
							940L3					
							940L4					
							940L5					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	S1 Short rotation arm	S With Anti-Glare Shield X Without Anti-Glare Shield	AO Opal Diffuser	XX N/A
CRI/CCT & Power	Control	IP	Body finish		
2700°K	C Built-in driver, non-dimmable D Built-in driver, DALI E Built-in driver, I-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth		
3000°K					
4000°K					

Length	Wiring
30 30 cm	BI Bottom feeding, Individual
60 60 cm	BB Bottom feeding, Beginning
90 90 cm	BM Bottom feeding, Middle
120 120 cm	BE Bottom feeding, End
	SI Side feeding, Individual
	SB Side feeding, Beginning
	SM Side feeding, Middle
	SE Side feeding, End

