

LIGHTWAY 5 – OUTDOOR / OPAL FLOOR MOUNTED, U BRACKET

The Lightway 5 outdoor opal is developed for homogenous lighting in harsh environments. This IP65 element benefits from a wide variety of outputs. The diffuser offers powerful lighting and excellent light transmission with high diffusion.

The fixture is available with an aluminum anti glare shield that gives control over the light for increased visual comfort.

- Superior optical transmission with no visible LED hotspots
- Wide, even levels of illumination
- High angle distribution to illuminate vertical & horizontal surfaces
- Great color mixing capability
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium




Optics

Optic Type: PMMA Opal Lens
Surface diffuser: Acrylic Opal Diffusing Lens

Electrical equipment

Mains Voltage: 220–240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curve



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / OPAL

FLOOR MOUNTED, U BRACKET

Code Index:

<u>L 5</u>	<u>O</u>	<u>F 1</u>		<u>A O</u>	<u>X X</u>	-----	-	<u>6 5</u>	--	---	--	
Family	Environment	Mounting	Glare Control	Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
			S				927L1	C		BS	30	SI
			X				927L2	D		WS	60	SB
							927L3	E		GS	90	SM
							927L4				120	SE
							930L1					
							930L2					
							930L3					
							930L4					
							930L5					
							940L1					
							940L2					
							940L3					
							940L4					
							940L5					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	F1 Floor mounted, U bracket	S With Anti-Glare Shield X Without Anti-Glare Shield	AO Opal Diffuser	XX N/A

CRI/CCT & Power	Control	IP	Body finish
<div>LED Load initial Lumen</div> <div>2700°K927L1: 10 W/m 1200 lm/m927L2: 15 W/m 1650 lm/m927L3: 22 W/m 2150 lm/m927L4: 30 W/m 3250 lm/m927L5: 42 W/m 4300 lm/m</div> <div>3000°K930L1: 10 W/m 1350 lm/m930L2: 15 W/m 1900 lm/m930L3: 22 W/m 2550 lm/m930L4: 30 W/m 3800 lm/m930L5: 42 W/m 5100 lm/m</div> <div>4000°K940L1: 10 W/m 1450 lm/m940L2: 15 W/m 2050 lm/m940L3: 22 W/m 2700 lm/m940L4: 30 W/m 4050 lm/m940L5: 42 W/m 5400 lm/m</div>	C Built-in driver, non-dimmable D Built-in driver, DALI E Built-in driver, I-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth

Length	Wiring
30 30 cm 60 60 cm 90 90 cm 120 120 cm	SI Side feeding, Individual SB Side feeding, Beginning SM Side feeding, Middle SE Side feeding, End

We reserve the right to make technical changes without prior notice

