

# LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES FLOOR MOUNTED, U BRACKET

The Lightway 5 outdoor symmetrical baffles is developed maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs & mountings. The baffles offer excellent glare control and are compatible with a wide array of beam angles, generating a powerful overall lighting effect.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptical
- Excellent glare control and visual cutoff. Transversal & longitudinal shielding angle (45°)
- Delivers High levels of light
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C




## Luminaire

**Product Type:** Ambient  
**Body Material:** Extruded aluminium

## Optics


**Optic Type:** UV stabilized TIR Lens  
**Glare Control Device:** Aluminium Anti-Glare Baffles  
**Surface diffuser:** No Diffuser




## Electrical equipment

**Mains Voltage:** 220-240 VAC 50/60 Hz  
**Control Gear Efficacy:** > 85%

## Polar Curve



Medium Beam, 30° /  
LOR: 64%



Wide Beam, 45° /  
LOR: 48.4%

We reserve the right to make technical changes without prior notice

# LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES

## FLOOR MOUNTED, U BRACKET

### Code Index:

<u>L 5</u>	<u>O</u>	<u>F 1</u>	<u>X</u>	<u>  </u>	<u>  </u>	<u>  </u>	<u>  </u>	<u>6 5</u>	<u>  </u>	<u>  </u>	<u>  </u>	
Family	Environment	Mounting	Glare Control	Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
					AB	30	92701	J		BS	30	SI
					AG	45	92702	K		WS	60	SB
					AW		92703	L		GS	90	SM
							93001				120	SE
							93002					
							93003					
							94001					
							94002					
							94003					

<b>Family</b>	<b>Environment</b>	<b>Mounting</b>	<b>Glare Control</b>	<b>Application</b>	<b>Beam Angle</b>
L5 Lightway 5	O Outdoor	F1 Floor mounted, U bracket	X Without Anti-Glare Shield	AB Black Symmetrical Baffles AG Gray Symmetrical Baffles AW White Symmetrical Baffles	30 Medium Beam, 30° 45 Wide Beam, 45°
<b>CRI/CCT &amp; Power</b>		<b>Control</b>	<b>IP</b>	<b>Body finish</b>	
	LED Load initial Lumen	J Remote driver, non-dimmable K Remote driver, DALI L Remote driver, 1-10V	65 IP65	BS Black Smooth WS White Smooth GS Gray Smooth	
2700°K	92701: 20 W/m 1950 lm/m 92702: 30 W/m 2700 lm/m 92703: 42 W/m 3600 lm/m				
3000°K	93001: 20 W/m 2150 lm/m 93002: 30 W/m 3000 lm/m 93003: 42 W/m 4000 lm/m				
4000°K	94001: 20 W/m 2350 lm/m 94002: 30 W/m 3200 lm/m 94003: 42 W/m 4250 lm/m				
<b>Length</b>	<b>Wiring</b>				
30 30 cm	SI Side feeding, Individual				
60 60 cm	SB Side feeding, Beginning				
90 90 cm	SM Side feeding, Middle				
120 120 cm	SE Side feeding, End				

We reserve the right to make technical changes without prior notice

