

LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES LONG ROTATION ARM

The Lightway 5 outdoor symmetrical baffles is developed maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs & mountings. The baffles offer excellent glare control and are compatible with a wide array of beam angles, generating a powerful overall lighting effect.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptical
- Excellent glare control and visual cutoff. Transversal & longitudinal shielding angle (45°)
- Delivers High levels of light
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium


Optics

Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220-240 VAC 50/60 Hz
Control Gear Efficacy: > 85%

Polar Curve



Medium Beam, 30° /
LOR: 64%



Wide Beam, 45° /
LOR: 48.4%

We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES

LONG ROTATION ARM

Code Index:

<u>L 5</u>	<u>O</u>	<u>S 2</u>	<u>X</u>	<u>---</u>	<u>---</u>	<u>-----</u>	<u>-</u>	<u>6 5</u>	<u>---</u>	<u>---</u>	<u>---</u>	
Family	Environment	Mounting	Glare Control	Accessory	Application	Beam Angle	CRI/CCT & Power	Control	IP	Body finish	Length	Wiring
					AB	30	92701	J		BS	30	BI
					AG	45	92702	K		WS	60	BB
					AW		92703	L		GS	90	BM
							93001				120	BE
							93002					SI
							93003					SB
							94001					SM
							94002					SE
							94003					

Family	Environment	Mounting	Glare Control Accessory	Application	Beam Angle
L5 Lightway 5	O Outdoor	S2 Long rotation arm	X Without Anti-Glare Shield	AB Black Symmetrical Baffles AG Gray Symmetrical Baffles AW White Symmetrical Baffles	30 Medium Beam, 30° 45 Wide Beam, 45°
CRI/CCT & Power			Control	IP	Body finish
2700°K	LED Load	initial Lumen	J Remote driver, non-dimmable	65 IP65	BS Black Smooth
	92701: 20 W/m	1950 lm/m	K Remote driver, DALI		WS White Smooth
	92702: 30 W/m	2700 lm/m	L Remote driver, 1-10V		GS Gray Smooth
3000°K	92703: 42 W/m	3600 lm/m			
	93001: 20 W/m	2150 lm/m			
	93002: 30 W/m	3000 lm/m			
4000°K	93003: 42 W/m	4000 lm/m			
	94001: 20 W/m	2350 lm/m			
	94002: 30 W/m	3200 lm/m			
	94003: 42 W/m	4250 lm/m			

Length	Wiring
30 30 cm	BI Bottom feeding, Individual
60 60 cm	BB Bottom feeding, Beginning
90 90 cm	BM Bottom feeding, Middle
120 120 cm	BE Bottom feeding, End
	SI Side feeding, Individual
	SB Side feeding, Beginning
	SM Side feeding, Middle
	SE Side feeding, End

We reserve the right to make technical changes without prior notice

