

LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES SHORT ROTATION ARM

The Lightway 5 outdoor symmetrical baffles is developed maximum performance in harsh environmental conditions. Made from extruded aluminum, this IP65 element benefits from a wide variety of outputs & mountings. The baffles offer excellent glare control and are compatible with a wide array of beam angles, generating a powerful overall lighting effect.

- Diverse options of beam angles: very narrow, narrow, medium, wide and elliptical
- Excellent glare control and visual cutoff. Transversal & longitudinal shielding angle (45°)
- Delivers High levels of light
- Integrates with any architecture.
- IK08
- Ta: -10 to 40°C



Luminaire

Product Type: Ambient
Body Material: Extruded aluminium


Optics

Optic Type: UV stabilized TIR Lens
Glare Control Device: Aluminium Anti-Glare Baffles
Surface diffuser: No Diffuser


Electrical equipment

Mains Voltage: 220–240 VAC 50/60 Hz
Control Gear Efficacy: > 85%



Polar Curve



Medium Beam, 30° /
LOR: 64%



Wide Beam, 45° /
LOR: 48.4%



We reserve the right to make technical changes without prior notice

LIGHTWAY 5 – OUTDOOR / SYMMETRICAL BAFFLES

SHORT ROTATION ARM

We reserve the right to make technical changes without prior notice



projects@vicelighting.com – www.vicelighting.com

Lebanon 11-0125-Beirut +961 1 486311 – France 75012 Paris +33 06 75 32 73 23

Code Index:

| <u>L 5</u> | <u>O</u> | <u>S 1</u> | <u>X</u> | <u>--</u> | <u>--</u> | <u>-----</u> | <u>-</u> | <u>6 5</u> | <u>--</u> | <u>----</u> | <u>--</u> |
|------------|-------------|------------|-------------------------|-------------|------------|-----------------|----------|------------|-------------|-------------|-----------|
| Family | Environment | Mounting | Glare Control Accessory | Application | Beam Angle | CRI/CCT & Power | Control | IP | Body finish | Length | Wiring |
| | | | | AB | 30 | 92701 | J | | BS | 30 | BI |
| | | | | AG | 45 | 92702 | K | | WS | 60 | BB |
| | | | | AW | | 92703 | L | | GS | 90 | BM |
| | | | | | | 93001 | | | | 120 | BE |
| | | | | | | 93002 | | | | | SI |
| | | | | | | 93003 | | | | | SB |
| | | | | | | 94001 | | | | | SM |
| | | | | | | 94002 | | | | | SE |
| | | | | | | 94003 | | | | | |

| Family | Environment | Mounting | Glare Control | Application | Beam Angle |
|-----------------|---|-------------------------------------|--|---|--|
| L5 Lightway 5 | O Outdoor | S1 Short rotation arm | X Without Anti-Glare Shield | AB Black Symmetrical Baffles AG Gray Symmetrical Baffles AW White Symmetrical Baffles | 30 Medium Beam, 30° 45 Wide Beam, 45° |
| CRI/CCT & Power | | | Control | IP | Body finish |
| | LED Load | initial Lumen | J Remote driver, non-dimmable K Remote driver, DALI L Remote driver, 1-10V | 65 IP65 | BS Black Smooth WS White Smooth GS Gray Smooth |
| 2700°K | 92701: 20 W/m 92702: 30 W/m 92703: 42 W/m | 1950 lm/m 2700 lm/m 3600 lm/m | | | |
| 3000°K | 93001: 20 W/m 93002: 30 W/m 93003: 42 W/m | 2150 lm/m 3000 lm/m 4000 lm/m | | | |
| 4000°K | 94001: 20 W/m 94002: 30 W/m 94003: 42 W/m | 2350 lm/m 3200 lm/m 4250 lm/m | | | |

| Length | Wiring |
|-------------------|--------------------------------------|
| 30 30 cm | BI Bottom feeding, Individual |
| 60 60 cm | BB Bottom feeding, Beginning |
| 90 90 cm | BM Bottom feeding, Middle |
| 120 120 cm | BE Bottom feeding, End |
| | SI Side feeding, Individual |
| | SB Side feeding, Beginning |
| | SM Side feeding, Middle |
| | SE Side feeding, End |