



FLEX 20 RGB



LUMINAIRE SPECIFICATION

Width	20mm
Height	18mm
Maximum length	5m and 13m options
Cut interval	100mm
Minimum bend diameter	>300mm
Material	White silicone
Mounting	Surface
IP Rating	IP67
Protection	UV, flame, salt and chlorine resistant
Standards	EN/AS/NZS 60598-2-1, 62031, 62471
Warranty	5 Years

LED SPECIFICATION

LED Wattage	12W/m
CCT	See options table below
Lumen package	R : 70lm/m, G : 160lm/m, B : 30lm/m
Lifetime (L70)	50,000hrs based on LM-80 & TM-21 applicable test data
Driver requirement	Constant voltage
Voltage	24VDC

ORDERING INFORMATION

MODEL	JACKET	CCT	LED TYPE	CABLE ENTRY	CONNECTOR IP	CABLE LENGTH	LENGTH
63S20V Neon Flex 20 Vertical Flat	1 White	RGB	S12 12W/m (5m max.)	E End	7 IP67	003 0.3m	.XXXX Length in mm
			L12 12W/m (13m max.)	B Bottom		010 1m	
63S20VD Neon Flex 20 Vertical Domed	1	RGB		SL Side Left	7	030 3m	
				SR Side Right		050 5m	
						100 10m	
	1	RGB			7		