



FLEX WALL WASHER - TUNABLE WHITE



LUMINAIRE SPECIFICATION

Dimensions	Flex : 25x26mm 25x29mm with fixings
Maximum length	5m Length = n cut intervals + 20mm
Cut interval	250mm
LED pitch	41.5mm
Minimum bend diameter	>400mm (Bendable in both planes)
Material	Silicone
Mounting	Surface
IP Rating	IP67
Optional accessories	Aluminium profile Stainless steel flexible profile

LED SPECIFICATION

LED Wattage	2x12W/m
LED Qty	24/m
CCT	See options table below
CRI	>90Ra
Optics	25°, 40°, 30x55°
Typical Lumen package	2700K : 630 lm/m 6000K : 740 lm/m
Binning	3 Step
Driver requirement	Constant voltage
Voltage	24VDC

ORDERING INFORMATION

MODEL	JACKET	CRI	CCT	CCT	LED TYPE	CABLE ENTRY	CONNECTOR IP	CABLE LENGTH	LENGTH		
63S2526L25	25°	1 White	C CRI >90	18 1800K	24 2400K	CT12 2x12W/m	E End	7 IP67	003 0.3m	.XXXX Length in mm	
63S2526L40	40°			2 2 Black					24 2400K		27 2700K
63S2526L3055	30x55°			27 2700K	30 3000K				030 3m		
				30 3000K					35 3500K		050 5m
				35 3500K					40 4000K		100 10m
				40 4000K					60 6000K		
					CT12	E	7				