


Description:

Low profile surface mounted direct wall Light. Various colour temperatures, IP54, finished in machined solid Brass (Aged) or 6061 Aluminium (Powder Coated), UV stabilised frosted Acrylic diffuser, pre-fitted 500mm lead, remote 24VDC constant voltage, 'Covert Mounting System'



Technical:

LED TYPE	COLORS D6240	CONTROL GEAR	REMOTE
RATED POWER	1W - 4W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE
INPUT POWER	24V DC	WEIGHT	0.2KG
NOMINAL LUMENS	70lm	HARDWARE	GLASS LENS, O-RING, GLAND, CABLE
IP RATING	IP54	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example 1525-AB-D-30-W-5W-DALI-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1525	AB Aged Brass	D Diffused	27 2700K	W Wall Mounted	1W / 24V DC	DALI	N/A
	NB Natural Brass		30 3000K		4W / 24V DC	0-10V	
	PB Black		40 4000K			PHASE	
	PW White					ON/OFF	

NL1525	-		-		-		-	
--------	---	--	---	--	---	--	---	--