

**Description:**

Belonging to the **Firefly Family** range, the Firefly Deco Pendant offers a simple, clean aesthetic with a decorative feature available in various colour temperatures, optics, finishes and control options. The Firefly Family offers a variety of products suitable for various applications. The products contain the same LED chip and optics for a consistent approach. Supplied with cable gland and double insulated cable. The Firefly Family also consists of a **Micro**, **XL** and **Standard Firefly** range creating a full suite of products.



**Technical:**

LED TYPE	XHP-50 Gen 2	CONTROL GEAR	REMOTE
RATED POWER	4W - 6W - 9W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SURFACE MOUNTED
INPUT POWER	350mA - 700mA - 1050mA / 6V	WEIGHT	1-2KG
NOMINAL LUMENS	300lm - 476lm - 780lm	HARDWARE	GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED METAL & HEATSINK
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

**Product Generator:** example 7038-BR-M-30-1-4W-1-1

Model	Finish	Beam Angle	CCT	Moun	Wa age	Dimming	Accessory
NL7038	AB Aged Brass	N Narrow 10°	27 2700K	1 Suspended 150mm	4W / 350mA	DALI	HC Honeycomb Louver
	NB Natural Brass	M Medium 21°	30 3000K	2 Suspended 350mm	6W / 700mA	0-10V	DL Diffuser Lens
	PB Black	W Wide 33°	40 4000K	3 Suspended 500mm	9W /1050mA	Phase	WS Wire suspension
	PW White	EL Elliptical 26°x41°		4 Suspended custom		On/Off	

NL7038	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---