

Description:

The Fox Bollard is a spike mounted pathway light designed to provide an even wash of light to the walkways. Available in various colour temperatures, IP65, machined solid brass (Aged), UV stabilized frosted acrylic diffuser, brass cable gland, pre-fitted double insulated exterior rated 500mm cable



Technical:

LED TYPE	COLORS D6240	CONTROL GEAR	REMOTE
RATED POWER	1W	DIMMING PROTOCOL	DALI - 0-10V - PHASE DIM - ON/OFF
CRI	80	CABLE LENGTH	500MM STANDARD LENGTH
BEAM ANGLES	NOMINATED IN TABLE BELOW	MOUNTING OPTIONS	SPIKE
INPUT POWER	24V DC CC	WEIGHT	ON REQUEST
NOMINAL LUMENS	190lm	HARDWARE	ACRYLIC, CABLE GLAND, CABLE
IP RATING	IP65	CONSTRUCTION	MACHINED SOLID BRASS
COLOUR TEMPERATURE	2700K - 3000K - 4000K	WARRANTY	2 YEARS

Product Generator: example NL1607CV-AB-D-30-SP-1W-DALI-N/A

Model	Finish	Beam Angle	CCT	Mounting	Wattage	Dimming	Accessory
NL1607CV	AB Aged Brass	D Diffused	27 2700K	SP Spike	1W / 24V DC	DALI	N/A
	NB Natural Brass		30 3000K			0-10V	
	PB Black		40 4000K			PHASE	
	PW White					ON/OFF	

NL1607	-	-	-	-	-	-	-
--------	---	---	---	---	---	---	---